

Xerox® VersaLink® C7120/C7125/C7130

Color Multifunction Printer



Xerox® VersaLink® C7100 Series Color Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.

System Specifications	VersaLink® C7120	VersaLink® C7125	VersaLink® C7130
One-sided Speed¹ 8.5 x 11 in./A4/210 x 297 mm	Up to 20 ppm (pages per minute) long edge feed (LEF)	Up to 25 ppm LEF	Up to 30 ppm LEF
8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 13 ppm Up to 11 ppm	Up to 16 ppm Up to 14 ppm	Up to 20 ppm Up to 17 ppm
Two-sided Speed¹ 8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 20 ppm LEF Up to 9 ppm Up to 8 ppm	Up to 25 ppm LEF Up to 10 ppm Up to 9 ppm	Up to 30 ppm LEF Up to 12 ppm Up to 11 ppm
Monthly Duty Cycle²	Up to 87,000 pages/month ²	Up to 107,000 pages/month ²	Up to 129,000 pages/month ²
Recommended Average Monthly Print Volume³	Up to 5,500 pages	Up to 6,250 pages	Up to 7,000 pages
Hard Drive	320 GB HDD (Optional on Desktop/Base Unit)		
Processor	1.05 GHz Dual-Core		
Memory	4 GB		
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a, Wi-Fi Direct, and Bluetooth (iBeacon) with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair		
Controller Features	Embedded Security and Integrity Control, TLS1.3 Support, NIST800-171r1 Compliance Print on Available Media, Mopria, Remote Install Wizard - Secure Fax Remote Enable/Disable, Air Print		
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Arabic, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian		

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Device Specifications				
Electrical Requirements				
North America	Voltage: 110-127 V -10%/+6% Frequency: 50/60 Hz +/-3%, 12A			
Europe and Other Geographies	Voltage: 220-240 V +/-10% Frequency: 50 Hz +/-3%, 8A			
Power Consumption				
Printing ⁴	For 110 V and 220 V: 20 ppm = 0.3 kWh or less; 25 ppm = 0.4 kWh or less; 30 ppm = 0.52 kWh or less			
Standby Mode ⁴	94 watts or less			
Sleep Mode ⁴	0.4 watts or less			
Operating Environment				
Required Temperature Range (Storage)	32 to 95°F (0 to 35°C)			
Required Temperature Range (Operating)	50 to 90°F (10 to 32°C)			
Required Relative Humidity	10% to 85%			
Sound Power Levels	Printing: 6.9 B(A) or less • 20 ppm = 6.45 B(A); 25 ppm = 6.50 B(A); 30 ppm = 6.9 B(A) Standby: 4.10 B(A) or less • 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A) Full System (including Finisher and HCF) Printing: 20 ppm = 7.15 B(A); 25 ppm = 7.18 B(A); 30 ppm = 7.35 B(A) Standby: 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A)			
Boot Time (from Off to UI Ready)	As fast as 60 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
Base Unit (Desktop Model)	23.23 in./590 mm	26.41 in./670.8 mm	30.18 in./766.5 mm	137.9 lbs./62.5 kg
Base Unit with Single Tray with Stand Module	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1117.2 mm	196 lbs./88.9 kg
Base Unit with High Capacity Tandem Tray Module	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1117.2 mm	220.5 lbs./100 kg
Base Unit with Three Tray Module	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1117.2 mm	200.4 lbs./90.9 kg
Base Unit with Three Tray Module and Office Finisher (with Booklet Maker)	44.69 in./1135.2 mm	26.71 in./678.6 mm	44.04 in./1117.2 mm	277.5 lbs./125.9 kg
Base Unit with Three Tray Module and Integrated Office Finisher	25.98 in./659.9 mm	26.41 in./670.8 mm	44.04 in./1117.2 mm	224.9 lbs./102 kg
Base Unit with Three Tray Module, Office Finisher, Booklet Maker, and High Capacity Feeder	57.1 in./1451.4 mm	26.71 in./678.6 mm	44.04 in./1117.2 mm	346 lbs./156.9 kg
Base Unit with High Capacity Tandem Tray Module and Integrated Office Finisher	26.3 in./668.0 mm	26.41 in./670.8 mm	44.04 in./1117.2 mm	244.9 lbs./111.1 kg
Base Unit with High Capacity Tandem Tray Module, Office Finisher, Booklet Maker, and High Capacity Feeder	57.1 in./1451.4 mm	26.71 in./678.6 mm	44.04 in./1117.2 mm	366 lbs./166 kg
Certifications				
To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .				

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer Configuration



130-sheet⁵ Single-pass Duplex Automatic Document Feeder (DADF) saves time by simultaneously scanning both sides of two-sided documents with up to 80 impressions per minute (ipm). High paper capacity drives productivity, especially for tasks that require large batches of scanned or copied documents.

The 100-sheet Bypass Tray handles media sizes from 3.5 x 3.87 in. to 11.69 x 17 in./88.9 x 98.4 mm to 297 x 431.8 mm.

User interface is an intuitive, tablet-like, 7-inch, tiltable touch screen that allows you to complete tasks in just a few effortless taps and lets you personalize your experience. Gain access to 100+ productivity apps through the **Xerox App Gallery**. Try it out at xerox.com/VersaLink7100U.


The standard 520-sheet⁵ Tray 1 handles media sizes from 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182 mm to 297 x 431.8 mm.




Card Reader Bay and embedded USB port.⁶

MAXIMIZE PAPER CAPACITY WITH ONE OF THESE FEEDING OPTIONS⁵


The Single Tray Module (optional with desktop model) increases total paper capacity to 1,140 sheets (includes Bypass Tray).




The Stand Module offers total paper capacity of 1,140 sheets (includes Bypass Tray) and provides storage for toner cartridges and other supplies




The Three Tray Module (optional with desktop model) increases total paper capacity to 2,180 sheets (includes Bypass Tray).




The Tandem Tray Module allows for total paper capacity of up to 3,140 sheets (includes Bypass Tray).



The High Capacity Feeder holds 2,000 sheets of Letter/A4 paper, increasing the maximum paper capacity to 5,140 sheets.



The Envelope Tray can replace Tray 1 to provide feeding of up to 60 envelopes.



INCREASE VERSATILITY WITH FINISHING OPTIONS⁵



The Office Finisher provides advanced finishing functions, 500-sheet stacker, 3-position stapling, and optional hole punch.



The Office Finisher with Booklet Maker simplifies booklet making, including score and saddle-stitch. Use it to create 64-page saddle-stitched booklets (2 to 16 sheets).



The Work Surface and Convenience Stapler staples up to 50 sheets and provides plenty of elbow room to sort documents.



The Dual Off-set Catch Trays⁷ stack up to 250 sheets each.



The Integrated Office Finisher provides 500-sheet stacking and 50-sheet, dual position stapling.

⁵Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.
⁶USB ports can be disabled.
⁷HDD and Dual Off-set Catch Trays are optional on Desktop model.

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Print	VersaLink® C7120	VersaLink® C7125	VersaLink® C7130
First-Print-Out Time	As fast as 8.8 seconds color	As fast as 8.8 seconds color	As fast as 7.0 seconds color
	As fast as 6.9 seconds black	As fast as 6.7 seconds black	As fast as 5.4 seconds black
Print Resolution	Up to 1200 x 2400 dpi		
Page Description Languages	PCL® 5e, 6 PDF TIFF JPEG HP-GL Adobe® PostScript® 3™ (Optional)		
Maximum Print Area	4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper		
Print Features	<ul style="list-style-type: none"> Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Finishing Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) LAN Fax (requires Fax Kit) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings 		
Print from USB	<ul style="list-style-type: none"> Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PDF/A 		
Operating Systems	<ul style="list-style-type: none"> Windows®, 7, 8, 8.1, 10, 11 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 Mac OS® version 10.12, 10.13, 10.14, 10.15, 11, 12 Citrix® Redhat® Enterprise Linux® Fedora Core SUSE® SAP® IBM® AIX® HP-UX® Oracle® Solaris <p>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.</p>		
Fonts	<ul style="list-style-type: none"> PostScript fonts: 136 PCL fonts: 83 		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage non-Xerox and Xerox® Devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management		
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy, and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos®, and others		

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Copy	VersaLink® C7120	VersaLink® C7125	VersaLink® C7130
Document Scanner	130-sheet Single-pass Duplex Automatic Document Feeder (DADF)		
Document Scanner Size	Platen: Up to 11.7 x 17 in./297 x 431.8 mm DADF: Up to 11.7 x 17 in./297 x 431.8 mm		
Simplex Copy Speed	Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)	Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)	Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)
Duplex Copy Speed	Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)	Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)	Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)
First-Copy-Out Time	As fast as 8.1 seconds color	As fast as 8.1 seconds color	As fast as 6.7 seconds color
	As fast as 5.7 seconds black	As fast as 5.7 seconds black	As fast as 4.4 seconds black
Sides (input:output)	1:1, 1:2, 2:2, and 2:1		
Quantity	1 to 999		
Resolution (max.)	Up to 600 x 600 dpi		
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments		
Concurrency	Concurrent scanning and printing		
Copy Features	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)* Auto-color Sensing Automatic Background Suppression Book Copying with Center Erase Booklet Copying* Collation Color Balance Color Effects Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Image Shift Lighten/Darken N-up Original Orientation Original Size Original Type Page Layout Reduce/Enlarge 25% to 400% Sample Copy Saturation Sharpness *Requires HDD/Productivity Kit		
Scan			
Capability	Black-and-white and color scanning		
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs		
Simplex Input Speed	Black-and-white: Scan up to 80 ipm – 8.5 x 11 in./A4 (210 x 297 mm) Color: Scan up to 80 ipm – 8.5 x 11 in./80 ipm A4 (210 x 297 mm)		
Duplex Input Speed	Black-and-white: Scan up to 80 ipm – 8.5 x 11 in./A4 (210 x 297 mm) Color: Scan up to 80 ipm – 8.5 x 11 in./80 ipm A4 (210 x 297 mm)		
Resolution	Optical – 600 x 600 dpi		
Bit Depth	24-bit color/8-bit grayscale		
Maximum Scan Area	Platen: 11.7 x 17 in./297 x 431.8 mm Document Feeder: 11.7 x 17 in./297 x 431.8 mm		
Network Filing Protocols	FTP SMTP SMB		

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Scan	
File Formats	JPG TIFF (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A
Scan Driver Compatibility (Network Only)	WIA TWAIN
Supported Scan Destinations	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)
Workflow Scanning (Optional Features)	
Scanning Apps and Xerox App Gallery	Scan to: DocuShare Go, Dropbox, Google Drive, Microsoft OneDrive, Microsoft 365, Box, Xerox® Workplace Mobile App (iOS/Android). See the full list of apps available in the Xerox App Gallery: xerox.com/AppGallery
PSTN One-Line or Three-Line Fax (Optional) Fax ⁸	
Fax Speed	33.6 Kbps
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
Fax Over IP (Optional)	
Compliance	T.38 compliant IP/SIP
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
Mobile and Cloud Ready	
Mobile Connectivity	Near Field Communication (NFC); Optional: Wi-Fi Direct, Wi-Fi (802.11 b/g/n/ac), AirPrint™ (iOS) including iBeacon (Bluetooth)
Mobile Printing	Mopria® Scan, Apple AirPrint™, Xerox® Print Service (Android), @PrintByXerox App; Optional: Xerox® Workplace Mobile App (iOS/Android), AirPrint™ (iOS) including iBeacon (Bluetooth)
Mobile Scanning	Mopria® Scan, Apple AirPrint™, Optional: Xerox® Workplace Mobile App (iOS/Android)
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® Content Management Platform (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)
Xerox® Workplace Central Platform	One-platform consistency for seamless productivity across computers, mobile devices, and printers. With the Workflow Central platform's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable, and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customer's time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and a cloud based-version (Workplace Cloud) of this solution

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Security	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication NIST800-171r1 Compliance Port Filtering Pre-installed Self-Signed Certificates Role-based Permissions Secure Email Secure Fax Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS1.3/SSL Support Trellix* – Embedded Control and Integrity Control Whitelisting *Requires HDD/Productivity Kit
Accounting	
Xerox® Standard Accounting/Network Accounting (Standard)	
Tracking	Copy, Print, Fax, Scan, and Email usage
Accounting	Xerox® Standard Accounting Feature Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job-based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server
Accounting Options – Network Accounting (Allows central server to manage all accounting)	
	<ul style="list-style-type: none"> Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and fax Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account

*Trellix formerly known as McAfee. Device firmware will reflect Trellix brand change in future software release.

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Paper Handling	
Document Feeder	
Capacity⁵	Single-pass Duplex Automatic Document Feeder (DADF): 130 sheets
Sizes	Custom sizes: 1.93 x 3.35 in. to 11.69 x 17 in./ 49 x 85 mm to 297 x 431.8 mm
Weights One-sided: Two-sided:	11 to 34 lb. bond/38 to 128 gsm 13 to 34 lb. bond/50 to 128 gsm
Bypass Tray	
Capacity⁵	100 sheets
Sizes	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in./88.9 x 98.4 mm to 297 x 431.8 mm
Weights	16 lb. bond to 80 lb. cover/60 to 216 gsm
Types	Bond Cardstock Custom Envelopes Glossy Cardstock Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Plain Paper Pre-printed Recycled
Tray 1	
Capacity⁵	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond Cardstock Custom Extra Heavyweight Labels Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Plain Paper Pre-printed Recycled

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Single Tray Module (Optional – Base Model Only)	
Capacity⁵	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond Cardstock Custom Envelopes Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Plain Paper Pre-printed Recycled
Single Tray Module with Stand (Optional)	
Capacity⁵	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond Cardstock Custom Envelopes Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Plain Paper Pre-printed Recycled

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Three Tray Module (Optional)	
Capacity⁵	Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond Cardstock Custom Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Heavyweight Labels Extra Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Plain Paper Pre-printed Recycled
High Capacity Tandem Tray Module (Optional)	
Capacity⁵	Tray 2: 520 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets
Sizes	Tray 2: Custom Sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm Tray 3: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5 Tray 4: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond Cardstock Custom Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Heavyweight Labels Extra Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Plain Paper Pre-printed Recycled

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Envelope Tray – Replaces Tray 1 (Optional)	
Capacity⁵	Up to 60 envelopes
Sizes	#10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm
Weights	20 to 25 lb. bond/75 to 90 gsm
High Capacity Feeder (Optional)	
Capacity⁵	2,000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 216 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Total Capacity	
Base Unit Capacity⁵	620 sheets
Single Tray Module Capacity⁵	1,140 sheets
Single Tray Module with Stand Capacity⁵	1,140 sheets
Three Tray Module Capacity⁵	2,180 sheets
High-Capacity Tandem Tray Capacity⁵	3,140 sheets
Finishing	
Finishing Output Trays (Optional on Base Model)	
Dual Off-set Catch Trays⁵	250 sheets each; Lower tray offsets
Integrated Office Finisher (Optional)	
Stacking Tray	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm
Weights	16 lb. bond to 80 lb. cover/60 to 256 gsm
Stapling	Dual Auto Stapling 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher (Optional)	
Capacity⁵	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4)
Sizes	5.8 x 5.8 in. to 11.7 x 17 in./148 x 148 mm to 297 x 432 mm
Weights	16 lb. bond to 80 lb. cover/60 to 220 gsm/Office Finisher GB up to 256 gsm
Multiposition Stapling	50 sheets of 24 lb. bond/90 gsm
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Booklet Maker for Office Finisher (Score/Crease, Saddle-Stitch Staple) (Optional)	
Capacity⁵	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF
Saddle-stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 80 lb. cover/64 to 220 gsm
Score/Crease	1-15 sheets/unstapled/52-105 gsm
Convenience Stapler and Work Surface (Optional)	
Capacity⁵	50-sheet stapling 5,000 staples Requires a separate outlet

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Device Management	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
Management Support	SNMP Version 1, SNMP Version 2c, and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Xerox® Easy Assist App
Xerox® CentreWare® Web Software	
	<ul style="list-style-type: none"> • A web-based server application for network administrators that permits web browser-based device management from any workstation, running Windows, UNIX, or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
Embedded Web Server – Integrated Device Web Page	
Device Status	<ul style="list-style-type: none"> • Tray Status/Contents • Consumables Status • Billing/Usage • Quick Links • Online Support
Print Queue Viewing	Job print queue management — view and delete
Job Submission	Print-ready files (PS (with optional PostScript option), PCL, PDF, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
Remote Services	
Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for the tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for output devices from Xerox based on actual usage, eliminating the need to manually manage supplies inventory

Xerox® VersaLink® C7120/C7125/C7130 Color Multifunction Printer

Supplies	Description	Yield
Sold Toner Cartridges	Cyan Magenta Yellow Black	18,500 standard pages ⁹ 18,500 standard pages ⁹ 18,500 standard pages ⁹ 31,300 standard pages ⁹
Metered Toner Cartridges	Cyan Magenta Yellow Black	20,300 standard pages 20,300 standard pages 20,300 standard pages 31,300 standard pages
Drum Cartridge	Black Cyan, Magenta, Yellow	109,000 standard pages ¹⁰ 87,000 standard pages ¹⁰
Waste Toner Bottle	1 Cartridge	30,000 pages
Booklet Maker Cartridge (8 cartridges per carton)	1 Cartridge Carton	16,000 staples (2,000 each cartridge)
Staple Refills for Finishers (3 refills per carton)	1 Refill Carton	15,000 staples (5,000 each refill)
Staple Cartridge for Finishers (1 cartridge per carton)	1 Cartridge	5,000 staples

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁶ USB ports can be disabled.

⁷ HDD and Dual Off-set Catch Trays are optional on Desktop model.

⁸ Requires analog phone line.

⁹ Average standard pages. Declared yield in accordance with ISO/IEC 19798. Toner yield can vary due to many factors including, but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes, and image quality set-points.

¹⁰ Approximate pages. Declared yield will vary depending on job run length, media size/orientation, and machine speed.

For more information, visit: <https://www.office.xerox.com/latest/SUPGL-01U.pdf>.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.